

9097250 TOSHIBA (DISCRETE/OPTO)

67C 09149

D T-27-01

≧ OVERSEA STANDARD ≦

Type No.		V _{CEO} (V)	I _C (mA)	P _C (mW)	h _{FE}		V _{CE(sat)} MAX.			f _T MIN.			C _{ob}		SW Time MAX.				MARK
NPN	PNP				V _{CE} (V)	I _C (mA)	V _{CE} (V)	I _C (mA)	I _B (mA)	(MHz)	V _{CE} (V)	I _C (mA)	(pF)	V _{CB} (V)	td (ns)	tr (ns)	tstg (ns)	tf (ns)	
*YTS3903	*YTS3905	40	200	200	1	10	0.3~0.4	50	5	250/200	20	35	35	175/175	50/60	7A/5A			
*YTS3904	*YTS3906	40	200	200	1	10	0.3/0.4	50	5	300/250	20	35	35	200/225	50/75	7B/5B			
*YTS4123	*YTS4125	30	200	200	1	2	0.3/0.4	50	5	250/200	20	—	—	—	—	7C/5C			
*YTS4124	*YTS4126	25	200	200	1	2	0.3/0.4	50	5	300/250	20	—	—	—	—	7D/5D			
*YTS4400	*YTS4402	40	600	200	1	150	0.75	500	50	200/150	10	15	20	225	30	7I/5I			
*YTS4401	*YTS4403	40	600	200	1	150	0.75	500	50	250/200	10	15	20	225	30	7J/5J			
*YTS2221	*YTS2906	30/40	600	200	10	150	1.6	500	50	250/200	20	—	—	—	—	7E/5E			
*YTS2222	*YTS2907	30/40	600	200	10	150	1.6	500	50	250/200	20	—	—	—	—	7G/5G			
*YTS2221A	*YTS2906A	40/60	600	200	10	150	1.0	500	50	250/200	20	10	25	225	60	7F/5F			
*YTS2222A	*YTS2907A	40/60	600	200	10	150	1.0	500	50	300/200	20	10	25	225	60	7H/5H			

* Under Development